

DECLARATION OF CONFORMITY

CERTIFICATE : GA-2024-03

TUS REPORT : RP-2024-43

TEST DATE : 4-Nov-2024

Society		F.III Gandossi Acciaierie Elettriche	
Head Office		24027 - Nembro (Bg) - Via Roma, 23	
Furnace ID	F1	Furnace Type	CHAMBER FURNACE
Furnace Chamber Dimensions		2800 x 3700 x 2300 H	
Furnace Working Zone (*)		1800 x 3200 x 1500 H	
Maximum Load Capacity		15 t	
Test Frequency	ANNUAL	Internal Test Procedure	Procedura prova uniformità API 6A (IO-02)

THE FURNACE COMPLIES WITH THE REQUIREMENTS OF

API 6A, 21st Ed. - Annex M

IN THE TEMPERATURE RANGE: 600,0 ÷ 1240,0°C (± 14,0°C)

IT CAN BE USED FOR TEMPERING, AGEING AND STRESS-RELIEVING
IN THE TEMPERATURE RANGE: 600,0 ÷ 900,0°C (± 8,0°C)

DECLARATION EXPIRY : 3-Nov-2025

NOTES

(*) The working zone is centered in the furnace. Basic supports, 500 mm high, are required

Approved by:
(GF-ELTI Srl)

JOB REF. : C/G4166S15

24060 - Sovere (Bg) - Viale Delle Industrie, 1 - Phone (00)39-035-966500 - Fax (00)39-035-966550
set.elti@gfelti.com

	☒ Review
	☐ Witness
Date: 5.11.2024	Name: _____

DECLARATION OF CONFORMITY

CERTIFICATE : GA-2024-03

TUS REPORT : RP-2024-43

TEST DATE : 4-Nov-2024

Society		F.lli Gandossi Acciaierie Elettriche	
Head Office		24027 - Nembro (Bg) - Via Roma, 23	
Furnace ID	F1	Furnace Type	CHAMBER FURNACE
Furnace Chamber Dimensions		2800 x 3700 x 2300 H	
Furnace Working Zone (*)		1800 x 3200 x 1500 H	
Maximum Load Capacity		15 t	
Test Frequency	ANNUAL	Internal Test Procedure	Procedura prova uniformità API 6D (IO-02)

THE FURNACE COMPLIES WITH THE REQUIREMENTS OF

API 6D, 25th Ed. - Annex H

IN THE TEMPERATURE RANGE: 600,0 ÷ 1240,0°C (± 14,0°C)

IT CAN BE USED FOR TEMPERING, AGEING AND STRESS-RELIEVING
IN THE TEMPERATURE RANGE: 600,0 ÷ 900,0°C (± 8,0°C)

DECLARATION EXPIRY : 3-Nov-2025

NOTES

(*) The working zone is centered in the furnace. Basic supports, 500 mm high, are required

Approved by:
(GF-ELTI Srl)

JOB REF. : C/G4166S15

24060 - Sovere (Bg) - Viale Delle Industrie, 1 - Phone (00)39-035-966500 - Fax (00)39-035-966550

set.elti@gfelti.com

	☒ Review
	☐ Witness
Date: 11/11/2024	Name: _____

DECLARATION OF CONFORMITY

CERTIFICATE : GA-2024-03

TUS REPORT : RP-2024-43

TEST DATE : 4-Nov-2024

Society		F.Ili Gandossi Acciaierie Elettriche	
Head Office		24027 - Nembro (Bg) - Via Roma, 23	
Furnace ID	F1	Furnace Type	CHAMBER FURNACE
Furnace Chamber Dimensions		2800 x 3700 x 2300 H	
Furnace Working Zone (*)		1800 x 3200 x 1500 H	
Maximum Load Capacity		15 t	
Test Frequency	ANNUAL	Internal Test Procedure	Procedura prova uniformità ASTM A991 (IO-04)

THE FURNACE COMPLIES WITH THE REQUIREMENTS OF

ASTM A991M - 22

IN THE TEMPERATURE RANGE: 600,0 ÷ 1240,0°C (± 14,0°C)

IT CAN BE USED FOR TEMPERING, AGEING AND STRESS-RELIEVING
IN THE TEMPERATURE RANGE: 600,0 ÷ 900,0°C (± 8,0°C)

DECLARATION EXPIRY : 3-Nov-2025

NOTES

(*) The working zone is centered in the furnace. Basic supports, 500 mm high, are required

(**) This TUS was conducted also in conformity to the Annex B requirements of Norsok M-650 4th ed.

Approved by:
(GF-ELTI Srl)

JOB REF. : C/G4166S15

24060 - Sovere (Bg) - Viale Delle Industrie, 1 - Phone (00)39-035-966500 - Fax (00)39-035-966550

set.elti@gfolti.com



DECLARATION OF CONFORMITY

CERTIFICATE : GA-2024-02

TUS REPORT : RP-2024-42

TEST DATE : 1-Nov-2024

Society		F.Ili Gandossi Acciaierie Elettriche	
Head Office		24027 - Nembro (Bg) - Via Roma, 23	
Furnace ID	F2	Furnace Type	CHAMBER FURNACE
Furnace Chamber Dimensions		2800 x 3700 x 2300 H	
Furnace Working Zone (*)		1800 x 3200 x 1500 H	
Maximum Load Capacity		15 t	
Test Frequency	ANNUAL	Internal Test Procedure	Procedura prova uniformità ASTM A991 (IO-04)

THE FURNACE COMPLIES WITH THE REQUIREMENTS OF

ASTM A991M - 22

IN THE TEMPERATURE RANGE: 600,0 ÷ 1150,0°C (± 14,0°C)

IT CAN BE USED FOR TEMPERING, AGEING AND STRESS-RELIEVING
IN THE TEMPERATURE RANGE: 600,0 ÷ 900,0°C (± 8,0°C)

DECLARATION EXPIRY : 31-Oct-2025

NOTES

(*) The working zone is centered in the furnace. Basic supports, 500 mm high, are required

(**) This TUS was conducted also in conformity to the Annex B requirements of Norsok M-650 4th ed.



Approved by:
(GF-ELTI Srl)

JOB REF. : C/G4166S15

DECLARATION OF CONFORMITY

CERTIFICATE : GA-2024-02

TUS REPORT : RP-2024-42

TEST DATE : 1-Nov-2024

Society		F.Ili Gandossi Acciaierie Elettriche	
Head Office		24027 - Nembro (Bg) - Via Roma, 23	
Furnace ID	F2	Furnace Type	CHAMBER FURNACE
Furnace Chamber Dimensions		2800 x 3700 x 2300 H	
Furnace Working Zone (*)		1800 x 3200 x 1500 H	
Maximum Load Capacity		15 t	
Test Frequency	ANNUAL	Internal Test Procedure	Procedura prova uniformità API 6D (IO-02)

THE FURNACE COMPLIES WITH THE REQUIREMENTS OF

API 6D, 25th Ed. - Annex H


IN THE TEMPERATURE RANGE: 600,0 ÷ 1150,0°C (± 14,0°C)

IT CAN BE USED FOR TEMPERING, AGEING AND STRESS-RELIEVING
IN THE TEMPERATURE RANGE: 600,0 ÷ 900,0°C (± 8,0°C)

DECLARATION EXPIRY : 31-Oct-2025

NOTES

(*) The working zone is centered in the furnace. Basic supports, 500 mm high, are required



Approved by:
(GF-ELTI Srl)

JOB REF. : C/G4166S15

DECLARATION OF CONFORMITY

CERTIFICATE : GA-2024-02

TUS REPORT : RP-2024-42

TEST DATE : 1-Nov-2024

Society		F.Ili Gandossi Acciaierie Elettriche	
Head Office		24027 - Nembro (Bg) - Via Roma, 23	
Furnace ID	F2	Furnace Type	CHAMBER FURNACE
Furnace Chamber Dimensions		2800 x 3700 x 2300 H	
Furnace Working Zone (*)		1800 x 3200 x 1500 H	
Maximum Load Capacity		15 t	
Test Frequency	ANNUAL	Internal Test Procedure	Procedura prova uniformità API 6A (IO-02)

THE FURNACE COMPLIES WITH THE REQUIREMENTS OF

API 6A, 21st Ed. - Annex M

IN THE TEMPERATURE RANGE: 600,0 ÷ 1150,0°C (± 14,0°C)

IT CAN BE USED FOR TEMPERING, AGEING AND STRESS-RELIEVING
IN THE TEMPERATURE RANGE: 600,0 ÷ 900,0°C (± 8,0°C)

DECLARATION EXPIRY : 31-Oct-2025

NOTES

(*) The working zone is centered in the furnace. Basic supports, 500 mm high, are required



Approved by:
(GF-ELTI Srl)

JOB REF. : C/G4166S15

24060 - Sovere (Bg) - Viale Delle Industrie, 1 - Phone (00)39-035-966500 - Fax (00)39-035-966550

set.elti@gfelti.com

DECLARATION OF CONFORMITY

CERTIFICATE : GA-2025-01

TUS REPORT : RP-2025-09

TEST DATE : 8-Feb-2025

Society		F.lli Gandossi Acciaierie Elettriche	
Head Office		24027 - Nembro (Bg) - Via Roma, 23	
Furnace ID	F3	Furnace Type	CHARIOT FURNACE
Furnace Chamber Dimensions		3130 x 5950 x 2300 H	
Furnace Working Zone (*)		2630 x 5450 x 1600 H	
Maximum Load Capacity		40 t	
Test Frequency	ANNUAL	Internal Test Procedure	Procedura prova uniformità API 6D (IO-02)

THE FURNACE COMPLIES WITH THE REQUIREMENTS OF

API 6D, 25th Ed. - Annex H

IN THE TEMPERATURE RANGE: 550,0 ÷ 950,0°C (± 14,0°C)


IT CAN BE USED FOR TEMPERING, AGEING AND STRESS-RELIEVING
IN THE TEMPERATURE RANGE: 550,0 ÷ 750,0°C (± 8,0°C)

DECLARATION EXPIRY : 7-Feb-2026

NOTES

(*) The working zone is centered in the furnace. Basic supports, 280 mm high, are required

JOB REF. : E4005S20



Approved by:
(GF-ELTI Srl)

[signature]

DECLARATION OF CONFORMITY

CERTIFICATE : GA-2025-01

TUS REPORT : RP-2025-09

TEST DATE : 8-Feb-2025

Society		F.Ili Gandossi Acciaierie Elettriche	
Head Office		24027 - Nembro (Bg) - Via Roma, 23	
Furnace ID	F3	Furnace Type	CHARIOT FURNACE
Furnace Chamber Dimensions		3130 x 5950 x 2300 H	
Furnace Working Zone (*)		2630 x 5450 x 1600 H	
Maximum Load Capacity		40 t	
Test Frequency	ANNUAL	Internal Test Procedure	Procedura prova uniformità API 6A (IO-02)

THE FURNACE COMPLIES WITH THE REQUIREMENTS OF

API 6A, 21st Ed. - Annex M

IN THE TEMPERATURE RANGE: 550,0 ÷ 950,0°C (± 14,0°C)

IT CAN BE USED FOR TEMPERING, AGEING AND STRESS-RELIEVING
IN THE TEMPERATURE RANGE: 550,0 ÷ 750,0°C (± 8,0°C)

DECLARATION EXPIRY : 7-Feb-2026

NOTES

(*) The working zone is centered in the furnace. Basic supports, 280 mm high, are required

JOB REF. : E4005S20



Approved by:
(GF-ELTI Srl)